

GasGard XL

Setting Standards of Excellence in Gas Monitoring

MSA's GasGard XL is a Multi-Channel Wall Mount Controller for monitoring toxic, oxygen and flammable gases in industrial plants. Due to its inherent versatility and ease of use, GasGard XL provides protection from potentially hazardous conditions in a variety of working environments and for virtually all health and safety applications.

GasGard XL offers reliability in a compact and robust wall mounted housing made from fire retardant ABS material grade.

The large, easy-to-read, multi-language LCD graphic display allocates real time information on target gas levels and events, allowing full system diagnosis, supported by individual LEDs per channel, relays and internal buzzer.

GasGard XL can be easily configured to accept up to eight remote gas sensors, depending on the number of individual plug-in input cards installed.

With two alarm levels per channel GasGard XL operates in conjunction with MSA's well-proven remote gas sensors (flammable and toxic or oxygen 4–20 mA) as well as with catalytic gas sensors.



Features and Benefits

- Expandable up to 8 independent channels using plug-in boards
- Robust wall mounted housing made from fire retardant ABS material grade
- Large graphic display with intuitive icons and all channels shown at a glance
- Dedicated keys make all functions accessible from the front panel
- Multi-language display selectable via menu
- Fully configurable by key/laptop via USB or RS 485 ModBUS connection
- Event log upload by galvanically isolated RS 485 or USB
- Ethernet ModBUS TCP/IP
- Common relay board for first and second Alarm Level, Horn 1 and 2 or Failure
- Internal buzzer 85 dB
- Manual and "one-man" calibration with stored values
- Safety Integrity Level SIL 2


Remote Gas Detectors

Catalytic Detectors	Series 47K-ST, Series 47K-HT, Series 47K-PRP, D-7010
Remote Sensor Transmitters	DF-7010, PrimaX I, PrimaX P, PrimaX IR, ULTIMA MOS-5, ULTIMA XL/XT Series, ULTIMA X Series, FlameGard Series, Standard 4–20 mA transmitters



Easy to Install

Thanks to it's efficient and ergonomic design, GasGard XL can be wired up and installed quickly and reliably. A large number of plugs for cabling glands allows a tidy cable routing and easy wiring.



Technical Specifications

Power Supply	85 VAC – 265 VAC 50/60 Hz 24 VDC nominal (range 18 – 32 VDC)
Sensor Power Supply	constant current 80 mA – 430 mA 18 – 32 VDC
Connection Modes	2, 3 wires
Terminal Board	Sensor connection for wires up to 2.5 mm ²
Input Signals	0-200 mV DC, 4-20 mA
Alarm Thresholds	ALARM 1 (Warning) adjustable from 5 to 100% f.s. (80% LEL for ATEX version) ALARM 2 (Alarm) adjustable from 5 to 100% f.s. (80% LEL for ATEX version)
Electronic Speed of Responsive	< 1s to reach 100% f.s.

Span/Zero Drift	$< \pm 0.5\%$ f.s. ± 1 digit/month	
Accuracy/Repeatability	< ±1% f.s. ±1 digit	
Operating Temperature	−10 °C − +50 °C	
Storage Temperature	−20 °C − +75 °C	
Ambient Humidity	90% RH non condensing	
Ingress Protection	IP56	
Approvals	ATEX 94/9/EC, EN 50270 (EMC), EN 50402, EN 61010-1 (Low Voltage Directive), EN 60079-29-1, SIL 2, CSA, CCCF	
Dimensions (W x H x D)	515 x 277 x 129 mm	
Weight	5 kg 8 kg (with battery)	
Housing Material	ABS plastic high resistant fire retardant grade UL-94 V-0	
Backup Battery	2.2 Ah (optional)	

Ordering Information

Description	Ordering No.
GasGard XL	
(incl.: housing, power supply 100 W, designed for up to four channels,	
common relays, without channel boards)	10090372
GasGard XL	
(incl.: housing, power supply 100 W, designed for up to eight channels,	
common relays, without channel boards)	10083905
Accessories	
Sensor extension board (for channels 5 – 8)	10081676
Channel relay board	10081677
Channel board 4–20 mA	10081674
Channel board mV (bridge pellistors)	10081675
Back-up battery pack (2.2 Ah) with holder & screws	10081772
EMC filter (to be used with ext. 24 VDC supply)	10081680

Please ask for the separate ordering sheet.

MSA (Britain) Limited
Lochard House
Linnet Way
Strathclyde Business Park
BELLSHILL
MI4 3RA
Phone +44 (0)16 98 5733 57
Fax +44 (0)16 98 74 01 41
E-mail info@msabritain.co.uk www.msabritain.co.uk

Subject to change without notice ID 07-515.2 GB/01/08.11

MSA Europe Thiemannstrasse 1 12059 Berlin

Germany
Phone +49 (0)30 68 86-0
Fax +49 (0)30 68 86-15 17
E-mail contact@msa-europe.com www.msa-europe.com

MSA International MSA international
1000 Cranberry Woods Drive
Cranberry Township, PA 16066
Phone +1 41296733 54
Fax +1 41296734 51
E-mail msa.international@msanet.com www.MSAnet.com

